

HARDWARE GUIDE - WLE1216V2-20

Component Map



Power Requirements

DC Power

Power Consumption 6.68 Watts (Max)

3.3V

miniPCle Slot Pin Assignment

Top side		Bottom side		
1	WAKE_L	2	+3.3V	
3	CHIP_PWD_L	4	GND	
5	NC	6	NC	
7	CLKREQ_L	8	NC	
9	GND	10	NC	
11	REFCLK-	12	NC	
13	REFCLK+	14	NC	
15	GND	16	NC	
Mechanical key				
17	NC	18	GND	
19	NC	20	WLAN_DISABLE_N	
21	GND	22	PERST_L	
23	PERn0	24	+3.3V	
25	PERp0	26	GND	
27	GND	28	NC	
29	GND	30	NC	
31	PETn0	32	NC	
33	PETp0	34	GND	
35	GND	36	NC	
37	GND	38	NC	
39	+3.3V	40	GND	
41	+3.3V	42	NC	
43	NC	44	LED_WLAN_L	
45	NC	46	NC	
47	NC	48	NC	
49	NC	50	GND	
51	NC	52	+3.3V	

GPIO Pin Mapping

miniPCle

Interface

GPIO Function				
GPIO Pin	Function	GPIO Pin	Function	
GPIO_17	WLAN_LED	GPIO_19	WD_N	
GPIO_20	I2C_SDA	GPIO_22	I2C_CLK	
GPIO_18	WLAN_DISABLE_N			

Copyright © Compex Systems. All rights reserved. COMPEX and the COMPEX logo, are registered trademarks of Compex Inc. Atheros and other trademarks are properties of their respective owners. While every effort is made to ensure the information is accurate, Compex does not accept liability for any errors or mistakes that may arise. All specifications are subject to change without notice.

