

# HARDWARE GUIDE - WLE600V5-27

## Component Map



MMCX Connectors Chain1 Chain0



#### GPIO Pin Mapping

GPIO Pin	Function	GPIO Pin	Function
GPIO_0	WLAN_DISABLE_L	GPIO_1	LED_WLAN_L
GPIO_19	ANT_A	GPIO_20	ANT_B

### Power Requirements

DC Power	3.3V for Module and 5V for PA	
Power Consumption	10 Watts (Max)	

#### miniPCle Slot Pin Assignment

Top side		Bottom side			
1	WAKE_L	2	+3.3V		
3	ANT_A	4	GND		
5	GPIO4	6	NC		
7	CLKREQ_L	8	NC		
9	GND	10	NC		
11	REFCLK-	12	NC		
13	REFCLK+	14	NC		
15	GND	16	NC		
Mechanical key					
17	NC	18	GND		
19	NC	20	W_DISABLE_L		
21	GND	22	RESET		
23	PERn0	24	+3.3V		

Тор	side	Bottor	n side
25	PERp0	26	GND
27	GND	28	NC
29	GND	30	NC
31	PETn0	32	NC
33	PETp0	34	GND
35	GND	36	USB_D-
37	NC	38	USB_D+
39	+3.3V	40	NC
41	+3.3V	42	NC
43	GND	44	LED_WLAN_L
45	+5V	46	NC
47	+5V	48	NC
49	+5V	50	GND
51	+5V	52	+3.3V

COMPEX

Copyright © Compex Systems. All rights reserved. COMPEX and the COMPEX logo, are registered trademarks of Compex Inc. Atheros and other trademarks are properties of their respective owners. While every effort is made to ensure the information is accurate, Compex does not accept liability for any errors or mistakes that may arise. All specifications are subject to change without notice.